

DESCRIPTION

Filler suitable for filling holes and cracks on interior and exterior walls. This paste is formulated with acrylic elastic copolymers and synthetic fibres and forms a coating resistant to micro cracking. It dries in a quick and homogeneous manner and does not require any pre-treatment. It keeps high elasticity levels over time event at temperatures below 0°C.

PRODUCT PROPERTY

	Value	Method
Adhesion to wood and building materials	Excellent	
Coverage	Good	
Elasticity	High	
Solid by weight	68-72 %	Internal PF25

SPECIFICATION DATA

	Value	Method
Drying time	Recoatable 4-5h fully 24h	Internal PF2

SHELF LIFE

1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

COLOUR RANGE

White

TYPICAL USE

Elasto Stucco is applied on existing cracks in one or more than one pass without the risk of further cracking. The surface requiring filling must be clean, dry and free from dust and uneven material. It is used in all cases where water or humidity infiltrations exist or are expected due to cracking caused by settlement or other reasons. Applied using a fabric falsework, it is ideal for non-adhering joints to the substrate or for the repair of very large cracking.

TOOLS

Spatula

THINNING

Ready to use.

APPLY

+5°C +30°C

SPECIFICATION ITEM

Filler suitable for filling holes and cracks on interior and exterior walls, to be applied with a spatula, ready for use.

INSTRUCTIONS

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.