

SKIN SOFT TOUCH FINITURA

Transparent finish with a soft-touch effect

DESCRIPTION

High quality Soft Touch transparent matt finish for interiors that gives the treated surface a pleasant velvety effect like soft skin. The product has a low environmental impact with close-to-zero emissions for the well-being of users and people living in the environment.

EMPLOYMENT

The product is suitable as a top coat for washable water-based paints and interior decorative paints. In particular, it can be applied as a topcoat after Skin Soft Touch Color Base to achieve a greater soft touch effect.

PRODUCT PROPERTY

	Value	Method
Solid by weight	32±2%	Internal PF25
Gloss	Gloss < 5	Internal PF6
Drying time	Dry to recoat 3h; Fully dry 5 days	Internal PF2

PERFORMANCE DATA

	Value	Method
Specific weight	970-1070 g/l	Internal PF3

SHELF LIFE

1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

COLOUR RANGE

Colourless transparent.
The colour could vary slightly from one production batch to the next; it is therefore important to finish the job with the same batch.

TOOLS

Roller, Spalter- Brush.

THINNING

Up to 10% by volume with water.

COVERAGE

19-21 m²/l per coat.

APPLY

+5°C +30°C

COATING SYSTEM

1-Plasterboard, cement plasters, gauged mortar plasters, hydraulic lime, skim coat, reinforced concrete, prefabricated concrete, old and new mould-free washable paints

Base coat

Sand the wood first with 80-grit sandpaper and then with 150-grit sandpaper. Apply one coat of Opakite W, 100-120 micron wet. After 6 hours, brush or sand with 180-grit paper and apply one or more coats of Ecolora Absolutecap to match.

Finish

After 3 hours, apply one or two coats of SKIN SOFT TOUCH FINITURA

SKIN SOFT TOUCH FINITURA

Transparent finish with a soft-touch effect

2-Substrates made of different types of wood

Base coat

Sand the wood first with 80 grit abrasive paper and then with 150 grit abrasive paper. Apply a 100-120 micron wet coat of Opakite W. After 6-8 hours, brush or sand with 180 grit paper and apply one or several coats of Ecolora Absolutecap in the same colour.

Finish

Apply as per point 1.

3-New substrates in iron, galvanized iron, aluminium or light alloys

Base coat

Thoroughly clean and remove any grease from the substrate with Nitro NV5000 Thinner. Apply Chromocap W on a dry substrate. After 8 hours, apply one or several coats of Ecolora Absolutecap in the same colour.

Finish

Apply as per point 1.

SPECIFICATION ITEM

High quality soft touch transparent matt finish based on acrylic/polyurethane resins in aqueous emulsion and special additives that give the treated surface a soft skin-like effect. The product is suitable for interiors as a finish for washable water-based paints with an average consumption of 100 ml/m².

INSTRUCTIONS

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23 °C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.