

PRODUCT DATA SHEET STUCCOCAP

Paste putty for smoothing ceilings and walls in interior



DESCRIPTION

Paste filler for interior application on wood or building materials. Wipe off dry. Adheres to various materials and is distinguished by good workability.

PRODUCT PROPERTY

	Value	Method
Adhesion to wood and building materials	GOOD	GOOD
Overcoatability with other products	GOOD	GOOD
Dry to touch on a 2 mm thickness	100-150 min	
Solid by weight	67-71 %	Internal PF25

PERFORMANCE DATA

	Value	Method
Specific weight	1710-1950 g/l	
Drying time	Recoatable 24h fully 5 days	Internal PF2

SHELF LIFE

1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

COLOUR RANGE

White.

TYPICAL USE

It is ideal on interior surfaces to fill holes, cracks and defects or to shave off woodwork, miscellaneous plaster coats, plasterboards and concrete. After sandpapering, it may be recoated with water- or solvent-based products. Tools should be washed with water immediately after use.

TOOLS

Spatula or Steel trowel.

THINNING

Ready to use.

APPLY

+5°C +30°C

SPECIFICATION ITEM

Interior paste filler for application on wood or building materials. Wipe off dry. It is ideal on interior surfaces for filling holes, cracks and defects or for skim coats both on wood and on various types of plaster finishes, plasterboard and concrete.

INSTRUCTIONS

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.