

DESCRIPTION

Water-based wall paint for interiors with high breathability, easy to apply, with drying times that allow rapid use of living areas, ideal for professional use, with high compatibility and adhesion characteristics, filling power and coverage on various types of substrate.

Its properties of adequate flow and low tendency to splash allow applications with manual or mechanical tools that ensure a finish of high aesthetic homogeneity and uniform opacity.

Thanks to its quality, it is the aesthetic and technical solution for different painting requirements with a good level of finish; it provides a film with low dust retention and resistant to rubbing. It is particularly breathable so as to avoid condensation in areas with a high concentration of water vapour such as kitchens and bathrooms; it ensures a high filling capacity and uniform opacity even on large surfaces in all light conditions. Particularly suitable for wool roller applications.

PRODUCT PROPERTY

	Class	Method	Value
	EN13300		
Opacity level (Contrast ratio)	4(10m ² /l)	UNI EN ISO 6504-3	< 95%
Gloss level	Very Matt	UNI EN ISO 2813	Gloss < 5
Dirt retention	low	UNI 10792	ΔL > 3 e ≤ 9
Wet scrub resistance	5	UNI EN ISO 11998	L _{dft} = 70 μ
Solid by weight		Internal PF25	66-68 %
Drying time		Internal PF2	recoatable 4-6h; fully 5 days
PERFORMANCE DATA	Specific weight	Internal PF3	1600-1700 g/l

SHELF LIFE

1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

COLOUR RANGE

White

TYPICAL USE

It is ideal for decorating and protecting new structures or structures undergoing maintenance that have a variety of substrates such as plasters with different compositions (cement, common lime, premixed), concrete and fibrocement, plasterboard, filler skims and old paint, and in all cases where quick and cost-effective maintenance is required, with excellent aesthetic results and at reasonable costs. For spray applications, ensure that the substrate is dust-free and avoid excessive atomization of the product by regulating the pressure, nozzle and thinning so as to ensure that the paint sprayed sufficiently wets the surface. On substrates subject to biological pollution due to mould, add 2 litres of anti-mould agent A10 for every 14 kg of paint.

TOOLS

Roller, Brush, Spray

TRASPICAP

Professional wall paint for interiors with high coverage

THINNING

Roller, brush: 20-35% by volume with water
Airless Spray: 0-10% by volume with water.

COVERAGE

6-8 m²/l one coat.

APPLY

+5°C +30°C

COATING SYSTEM

Cement-based and gauged mortar plasters, new and old mould-free washable paint
Cement-based and gauged mortar plasters, new and old mould-free washable paint

1. Remove any traces of dust, and stop up any imperfections with *Stucco Light* filler.
2. Apply *Traspicap* in two coats on a dry substrate, 4-6 hours apart.

Hydraulic lime-based plasters, reinforced concrete, concrete prefabs, plaster skims, filler skims, plasterboard, tempera paint and other highly absorbent substrates

First apply an undercoat of *Acrifix* diluted in water in mixing proportions of 1:5, or *Coprisol* and proceed as per point 2.

SPECIFICATION ITEM

Breathable water paint for interiors formulated with synthetic resins and with a solid residue about 70%, to be applied with an average consumption of 280 ml/m².

INSTRUCTIONS

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.