

# Techcoat Pro

Transparent protective two-component finish



Transparent two-component acrylic paint, non-yellowing, water-repellent, suitable for indoor and outdoor use for the protection of concrete and micro cement surfaces or finished with decorative effects (including lime-based decorative finishes). Techcoat Pro guarantees high resistance to water, abrasion, stomping and scratches.

**Ideal in the field of civil construction for private or commercial use such as shops, apartments, hotels, showrooms, offices, museums and public buildings.**

Linea **GENERATION ART**



**GREAT ELASTICITY**  
**EXCELLENT RESISTANCE TO WASHING**  
**FAST DRYING**



**GLOSSY, SEMI-GLOSSY**  
**AND MATTE FINISH**  
**HOMOGENEOUS FINISH**



**EASY TO APPLY**  
**HOMOGENEOUS OPACITY**  
**ON LARGER SURFACES**



**ARREGHINI®**  
ITALIAN PAINTS SINCE 1950

# Techcoat Pro

## Transparent protective two-component finish

### COMPOSITION

Product formulated with fine hydroxyl acrylic resins in aqueous emulsion, selected opacifiers and aliphatic polyisocyanate.

### CHARACTERISTICS

Transparent two-component acrylic paint, non-yellowing, water-repellent, suitable for indoor and outdoor use. Techcoat Pro guarantees high resistance to water, abrasion, stamping and scratches.

### FIELD OF USE


It is used for the protection of concrete and micro-cement surfaces and decorative coatings, including lime-based products, on vertical and horizontal surfaces. Techcoat Pro must be applied in double layers.

### TECHNICAL CHARACTERISTICS OF THE PRODUCT

APPLICATION	Roller, brush, spray.
SURFACE	Concrete, micro cement decorative finishes (also lime-based)
YIELD	6.5 -7 m <sup>2</sup> /l in double layer (cons. rate: 150 g/m <sup>2</sup> x 2 layers)
GLOSS	gloss, semigloss, matt
DRY RESIDUE	Comp. A: 32% ± 2 and A + B: 40% ± 2
DRYING TIME	stackable 4h, complete 5 days
MIXING RATIO	100:25 with Induritore 1 in weight and in volume
DILUTION	10% in volume with water
APPLICATION TEMPERATURE	+15°C +30°C

For more information on the product and the application cycle, consult the technical data sheet downloadable from [www.caparreghini.it](http://www.caparreghini.it).

### COLORS AVAILABLE IN STOCK



TRANSPARENT | CLEAR

PACKAGING: 4L



**CAP ARREGHINI SpA**

ITALIAN PAINTS SINCE 1950

V.le Pordenone, 80 - 30026 PORTOGRUARO (VE)

Tel. +39 0421 278111 - Fax +39 0421 278115

[info@caparreghini.it](mailto:info@caparreghini.it) - [www.caparreghini.it](http://www.caparreghini.it)

Azienda con Sistema Certificato UNI EN ISO 9001 - UNI EN ISO 14001

follow us on



[www.caparreghini.it](http://www.caparreghini.it)

  
made in Italy